

Project Name:	
Catalog Number:	Fixture Type:
Volts / Watts:	Lamps / Board:



FLAT STRIP 4FT - 44W LED

COMMERCIAL

FEATURES

- Embedded LED's Provide Sleek Low Profile
- Frosted Acrylic Lens Lays Flush
- .040" Aluminum Pre-Painted White Housing
- 3000K-5000K Color Options
- Ceiling, Wall, or Suspension Mounting Options
- Multiple Dimming and Control Options
- Suitable for Installing in Continuous Runs
- 0-10V Dimming Driver (Std.)*
- 5 Year Warranty
- DesignLights Consortium® Premium Qualified Luminaire

*To Ensure Lead Wires Are Attached, "DIM" Call Out Is Required When Building Part Number

**FOR 44W MODEL, ONLY 5000K IS CURRENTLY DLC PREMIUM!
(ALL OTHER COLOR TEMPS OF 44W MODEL HAVE STANDARD DLC LISTING)



LED SYSTEM

Calculated L70 (TM-21)	>100K
Delivered Lumens	4,859lm
Total Input Watts	44W
Luminaire Efficacy Rating (LER)	110lm/W
Correlated Color Temperature (CCT)	5000K
Color Rendering Index (CRI)	>80
Max Ambient Temp	108°F
Min Ambient Temp	-4°F
Universal Driver	120-277V

LED System data above based on FF4-44WLED-UNIV-50
LED Lumen Maintenance Estimates based on TM-21 projections for the light source at 25°C ambient

SUITABLE APPLICATIONS

- Schools
- Offices
- Hallways
- Bathrooms



ORDERING GUIDE

FF4	44WLED	UNIV	40	eg: CORDx
-----	--------	------	----	-----------


Series	LED	Driver	Color	Options
--------	-----	--------	-------	---------

<input type="checkbox"/> FF4	Flat Strip 4ft	<input type="checkbox"/> 44WLED	<input type="checkbox"/> UNIV 120-277V Driver	<input type="checkbox"/> 30 <input type="checkbox"/> 35 <input type="checkbox"/> 40 <input type="checkbox"/> 50**	<input type="checkbox"/> CORDx <input type="checkbox"/> MCWHIPx <input type="checkbox"/> FIOS <input type="checkbox"/> USBD <input type="checkbox"/> BDxx <input type="checkbox"/> BLD <input type="checkbox"/> DIM <input type="checkbox"/> SD480* <input type="checkbox"/> SD347* <input type="checkbox"/> FMB <input type="checkbox"/> HOOK <input type="checkbox"/> HUB 3/4" Conduit <input type="checkbox"/> HB-60-18Y-PAD <input type="checkbox"/> ES <input type="checkbox"/> ES/PCD	Cord (x = ft) Flexible Conduit (x = ft) On/Off Occupancy Sensor Installed User Select Bi-level Dim w/ Occ. Sensor Preset Bi-Level Dim Sensor (xx=% e.g. 20, 30) Bi-Level Dim Driver (2 Hot Leads) Dimming Leads Added 480V Step Down Transformer 347V Step Down Transformer Fixture Mounting Box Cast Iron, Single-Point Mount (Must Be Used w/ FMB) For Pendant Mounting (Must Be Used w/ FBM) Adjustable 60" Y-Pad Hanger Set EasySense Control Pre-Installed App On Control Device
			*Not Currently DLC Listed w/ This Option			
			**Only DLC Premium w/ 5000K (3000K-4000K is listed under DLC Standard Only)			


FLAT STRIP 4FT - 44W LED

COMMERCIAL


TOP ASSEMBLY VIEW



SIDE ASSEMBLY VIEW



END ASSEMBLY VIEW




MOUNTING OPTIONS

- **HUB 3/4" Conduit** - For Pendant Mounting (Must use w/ FMB for Single Mount)
- **Y-Toggle Cable Kit** - Includes 2 Adjustable 60" Y-Pad Cable Hangers
- **HOOK** - Cast Iron, Single-Point Mount (Must use w/ FMB)
- **Fixture Mounting Box (FMB)** - Includes Rigid Box to Attach to the Fixture, Provides for Single Point Mounting to Accept Hook or Conduit Hub (sold separately).



HB-60-18Y-PAD



FMB



HUB 3/4"
CONDUIT




HOOK

FF4-44WLED-UNIV-50

SUMMARY DATA

HEMISPHERES TESTED:	BOTH
EFFICIENCY (Total):	100.0 %
EFFICIENCY (Downlight)	100.0 %
EFFICIENCY (Uplight):	0.0 %
CIE CLASSIFICATION:	DIRECT
SPACING CRITERION (0-Deg.):	1.22
SPACING CRITERION (90-Deg.):	1.20
LUMENS/LAMP:	4602.371
NO. OF LAMPS:	1
LUMINOUS OPENING: RECTANGULAR	
Width:	0.15 (Feet)
Length:	3.67
Height:	0.00
INPUT WATTS:	44.68

PLANE AND CONE DIAGRAM



Photometric values based upon tests performed in compliance with LM-79. IES files can be downloaded at www.ilp-inc.com

Industrial Lighting Products

LED
lighting facts
A Program of the U.S. DOE

Light Output (Lumens)	4788
Watts	44.12
Lumens per Watt (Efficacy)	108.52

Color Accuracy Color Rendering Index (CRI)	80
--	-----------

Light Color
Correlated Color Temperature (CCT) **4000 (Bright White)**

2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008: *Approved Method for the Electrical and Photometric Testing of Solid-State Lighting*. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: -E34NMK (8/18/2016)
Model Number: FF4-44WLED-UNIV-40
Type: Luminaire - Linear