

Project Name:

Part Number:

RACK AISLE HIGH BAY - 80W LED

8 ft HIGH BAY



407-478-3759
www.ilp-inc.com

FEATURES

- Aluminum body with riveted construction and high gloss polyester white paint
- 95% Enhanced aluminum narrow distribution reflector
- Multiple dimming & sensor options to fully control occupied and unoccupied light levels
- Single fixture or continuous row
- 4000K and 5000K color options
- 5 year warranty
- ETL Damp listed
- 0-10V Dimmable Driver
- DesignLight Consortium® Premium Qualified Luminaire*

* Qualified as a direct linear ambient and high-bay aisle luminaire



SUITABLE APPLICATIONS

- Aisleways
- Warehouses
- Distribution Centers
- Manufacturing Plants

LED SYSTEMS INFORMATION	4000K	5000K
Calculated L ₇₀ (TM-21)	>100K	>100K
Delivered Lumens	12,260 lm	12,595 lm
Total Input Watts	80 W	80 W
Luminaire Efficacy Rating (LER)	154 lm/W	158 lm/W
Correlated Color Temperature (CCT)	4000K	5000K
Color Rendering Index (CRI)	>80	>80
Maximum Ambient Temperature	125°F	125°F
Minimum Ambient Temperature	-40°F	-40°F
Universal Driver	120-277 V	120-277 V

LED System data above based on RAH8-80WLED-UNIV-40 & RAH8-80WLED-UNIV-50
LED Lumen Maintenance Estimates based on TM-21 projections for the light source at 25°C ambient.


ORDERING GUIDE:

Series	Watts	Driver	Color	Options
RAH8 Aisle Bay 8ft	80WLED	UNIV 120-277V Driver HV 347-480V Driver	50 40	WC* FIOS FIOS/PC USDC USBD BDxx BDxxPC FIOSPC/DLH AB HB-XX-18Y-PAD SD480* F//ILBCP05 F//ILBCP07 F//ILBCP10 F//ILBCP12
				Wire Cage On/Off Occupancy Sensor Installed On/Off Occupancy Sensor w/ Photocell User Selectable Dimming Control User Select Bi-level Dim w/ Occ. Sensor Preset Bi-Level Dim Sensor (xx=%eg.20,30) Preset Bi-Level Dim Sensor with Photocell Daylight Harvesting Bracket for Continuous Row Y-Toggle Cable System (XX = in) 480V Step Down Transformer 5W LED Factory Installed Battery Backup 7W LED Factory Installed Battery Backup 10W LED Factory Installed Battery Backup 12W LED Factory Installed Battery Backup

* Option does not meet DLC

RACK AISLE HIGH BAY - 80W LED

8ft HIGH BAY




MOUNTING OPTIONS

- **V-Clips** - Dual point chain or cable hanging (std.)
- **HB-XX-18Y-PAD** - Includes two adjustable cable hangers
- **SMBZKIT** - Surface mount bracket kit. Provides a 2" space above the fixture.



V-CLIPS



HB-XXX-PAD




SMBZKIT

RAH8-80WLED-UNIV-50

SUMMARY DATA

EFFICIENCY (Downlight):	100.0 %
EFFICIENCY (Uplight):	0.0 %
CIE CLASSIFICATION:	DIRECT
SPACING CRITERION (0-Deg.):	1.31
SPACING CRITERION (90-Deg.):	0.64
LUMENS:	11419.99
INPUT WATTS:	79.85

CANDELA PLOT



Photometric values based upon tests performed in compliance w/ LM-79.
 Download IES files at www.ilp-inc.com