



TROFFER SELECTION GUIDE



SUITABLE APPLICATIONS		VOLA	FLT	VAT 	VOL	PAN	VPAN 
	EDUCATION	✓	✓	✓	✓	✓	✓
	HEALTHCARE	✓	✓	✓	✓	✓	✓
	COMMERCIAL OFFICE	✓	✓	✓	✓	✓	✓
	RETAIL	✓	✓	✓	✓	✓	✓
	VANDAL RESISTANT		✓			✓	✓
	CONVENIENCE STORE					✓	✓
	COMMERCIAL KITCHEN					✓	
	FOOD PREP					✓	
FEATURES & PERFORMANCE	LUMEN RANGE	2,400 – 10,000	2,300 – 4,800	2,500 – 7,500 (Lumen Selectable)	2,800 – 7,000	2,300 – 7,500	2,600 – 7,000 (Lumen Selectable)
	EFFICACY (lm/W) UP TO	151	125	148	135	132	127
	CRI	80, 90	80	80	80	80	80
	CCT OPTIONS	30, 35, 40, 50	30, 35, 40	30,35, 40 (CCT Selectable)	35, 40	35, 40	35, 40
	VOLTAGE	120-277V – Opt. 347V	120-277V – Opt. 347V	120-277V – Opt. 347V	120-277V – Opt. 347V	120-277V – Opt. 347V	120-277V – Opt. 347V
	SIZES	1X4, 2x2, 2x4	1X4, 2x2, 2x4	1X4, 2x2, 2x4	2x2, 2x4	1X4, 2x2, 2x4	1X4, 2x2, 2x4
	DIFFUSER STYLE	VOLUMETRIC	FLAT	VOLUMETRIC	VOLUMETRIC	FLAT	FLAT
	AIR RETURN	YES	NO	NO	NO	NO	NO
	MOUNTING	GRID, FLANGE, SURFACE	GRID, FLANGE, SURFACE	GRID, FLANGE, SURFACE	GRID, FLANGE	GRID, FLANGE, SURFACE, SKY LIGHT	GRID, FLANGE, SURFACE, SUSPENDED
	RATINGS	DAMP, ETL, IC	DAMP, ETL, IC	DAMP, ETL, IC	DAMP, UL, IC	DAMP, UL, IC	DAMP, UL, IC
	WARRANTY	5 YEAR (OPT. 10 YEAR)	5 YEAR (OPT. 10 YEAR)	5 YEAR (OPT. 10 YEAR)	5 YEAR (OPT. 10 YEAR)	7 YEAR (OPT. 10 YEAR)	5 YEAR
	DLC LISTING	PREMIUM	STANDARD	PREMIUM	PREMIUM	PREMIUM	STANDARD
	BAA COMPLIANT	YES	YES	NO	NO	NO	NO
	RETROFIT KIT OPTION	YES	YES	YES	YES	NO	NO
ADVANCE GROUPING CONTROLS	EASYSENSE	✓	✓	✓		✓	
	ENLIGHTED	✓	✓	✓		✓	
	LUTRON	✓	✓	✓		✓	