

IES ROAD REPORT**PHOTOMETRIC FILENAME : SAM-36L-U-40-T5S.IES****DESCRIPTIVE INFORMATION (From Photometric File)**

IESNA:LM-63-2002

[TEST]

[TESTLAB]

[TESTDATE]

[ISSUEDATE]

[LAMPPOSITION] 0,0

[MANUFAC] Industrial Lighting Products Inc

[LUMCAT] SAM-36L-U-40-T5S

[LUMINAIRE] Skyline Medium, 36,000 Lumens, 4000K, Type 5 Square Optic

[LAMP] N/A

CHARACTERISTICS


IES Classification	Type VS
Longitudinal Classification	Short
Lumens Per Lamp	37249 (1 lamp)
Total Lamp Lumens	37249
Luminaire Lumens	37249
Downward Total Efficiency	100 %
Total Luminaire Efficiency	100 %
Luminaire Efficacy Rating (LER)	160
Total Luminaire Watts	233.1
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	22560.416
Maximum Candela Angle	310H 70V
Maximum Candela (<90 Degrees Vertical)	22560.416
Maximum Candela Angle (<90 Degrees Vertical)	310H 70V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Lamp Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	3807.385 (10.2% Lamp Lumens)
Cutoff Classification (deprecated)	Semi-Cutoff

IES ROAD REPORT
PHOTOMETRIC FILENAME : SAM-36L-U-40-T5S.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	1009.4	2.7	2.7
FM - Front-Medium (30-60)	8090.9	21.7	21.7
FH - Front-High (60-80)	10181.1	27.3	27.3
FVH - Front-Very High (80-90)	136.1	0.4	0.4
BL - Back-Low (0-30)	948.0	2.5	2.5
BM - Back-Medium (30-60)	6696.7	18.0	18.0
BH - Back-High (60-80)	10073.3	27.0	27.0
BVH - Back-Very High (80-90)	113.8	0.3	0.3
UL - Uplight-Low (90-100)	0.0	0.0	0.0
UH - Uplight-High (100-180)	0.0	0.0	0.0
Total	37249.3	99.9	100.0
BUG Rating	B5-U0-G4		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Lamp
Downward Street Side	19417.5	52.1
Downward House Side	17831.9	47.9
Downward Total	37249.4	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	37249.4	100.0

POLAR GRAPH




Maximum Candela = 22560.416 Located At Horizontal Angle = 310, Vertical Angle = 70
1 - Vertical Plane Through Horizontal Angles (310 - 130) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (70) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=1009.4, Medium=8090.9, High=10181.1, Very High=136.1
Back: Low=948.0, Medium=6696.7, High=10073.3, Very High=113.8
Uplight: Low=0.0, High=0.0

BUG Rating : B5-U0-G4