

IES ROAD REPORT

PHOTOMETRIC FILENAME : SAM-24L-U-40-T3.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST]

[TESTLAB]

[TESTDATE]

[ISSUEDATE]

[LAMPPOSITION] 0,0

[MANUFAC] Industrial Lighting Products Inc

[LUMCAT] SAM-24L-U-40-T3

[LUMINAIRE] Skyline Medium, 24,000 Lumens, 4000K, Type 3 Optic

[LAMP] N/A

CHARACTERISTICS


IES Classification	Type III
Longitudinal Classification	Short
Lumens Per Lamp	23803 (1 lamp)
Total Lamp Lumens	23803
Luminaire Lumens	23803
Downward Total Efficiency	100 %
Total Luminaire Efficiency	100 %
Luminaire Efficacy Rating (LER)	153
Total Luminaire Watts	155.3
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	17133.34
Maximum Candela Angle	300H 65V
Maximum Candela (<90 Degrees Vertical)	17133.34
Maximum Candela Angle (<90 Degrees Vertical)	300H 65V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Lamp Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	1774.379 (7.5% Lamp Lumens)
Cutoff Classification (deprecated)	Full Cutoff

IES ROAD REPORT
PHOTOMETRIC FILENAME : SAM-24L-U-40-T3.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	1530.3	6.4	6.4
FM - Front-Medium (30-60)	9460.6	39.7	39.7
FH - Front-High (60-80)	7354.2	30.9	30.9
FVH - Front-Very High (80-90)	206.6	0.9	0.9
BL - Back-Low (0-30)	909.3	3.8	3.8
BM - Back-Medium (30-60)	2688.7	11.3	11.3
BH - Back-High (60-80)	1563.9	6.6	6.6
BVH - Back-Very High (80-90)	89.4	0.4	0.4
UL - Uplight-Low (90-100)	0.0	0.0	0.0
UH - Uplight-High (100-180)	0.0	0.0	0.0
Total	23803.0	100.0	100.0
BUG Rating	B3-U0-G3		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Lamp
Downward Street Side	18551.7	77.9
Downward House Side	5251.2	22.1
Downward Total	23802.9	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	23802.9	100.0

POLAR GRAPH




Maximum Candela = 17133.34 Located At Horizontal Angle = 300, Vertical Angle = 65
1 - Vertical Plane Through Horizontal Angles (300 - 120) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (65) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=1530.3, Medium=9460.6, High=7354.2, Very High=206.6
Back: Low=909.3, Medium=2688.7, High=1563.9, Very High=89.4
Uplight: Low=0.0, High=0.0

BUG Rating : B3-U0-G3