

IES ROAD REPORT

PHOTOMETRIC FILENAME : SAS-6L-U-40-T2.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST]
[TESTLAB]
[TESTDATE]
[ISSUE DATE]
[LAMP POSITION] 0,0
[MANUFAC] Industrial Lighting Products Inc
[LUMCAT] SAS-6L-U-40-T2
[LUMINAIRE] Skyline Small, 6,000 Lumens, 4000K, Type 2 Optic
[LAMP] N/A

CHARACTERISTICS


IES Classification	Type II
Longitudinal Classification	Medium
Lumens Per Lamp	6803 (1 lamp)
Total Lamp Lumens	6803
Luminaire Lumens	6803
Downward Total Efficiency	100 %
Total Luminaire Efficiency	100 %
Luminaire Efficacy Rating (LER)	154
Total Luminaire Watts	44.2
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	5612.722
Maximum Candela Angle	290H 71V
Maximum Candela (<90 Degrees Vertical)	5612.722
Maximum Candela Angle (<90 Degrees Vertical)	290H 71V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Lamp Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	1551.991 (22.8% Lamp Lumens)
Cutoff Classification (deprecated)	Non-Cutoff

IES ROAD REPORT
PHOTOMETRIC FILENAME : SAS-6L-U-40-T2.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	786.3	11.6	11.6
FM - Front-Medium (30-60)	2964.7	43.6	43.6
FH - Front-High (60-80)	1699.8	25.0	25.0
FVH - Front-Very High (80-90)	75.5	1.1	1.1
BL - Back-Low (0-30)	324.2	4.8	4.8
BM - Back-Medium (30-60)	621.6	9.1	9.1
BH - Back-High (60-80)	323.0	4.7	4.7
BVH - Back-Very High (80-90)	8.0	0.1	0.1
UL - Uplight-Low (90-100)	0.0	0.0	0.0
UH - Uplight-High (100-180)	0.0	0.0	0.0
Total	6803.1	100.0	100.0
BUG Rating	B1-U0-G1		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Lamp
Downward Street Side	5526.3	81.2
Downward House Side	1276.8	18.8
Downward Total	6803.1	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	6803.1	100.0

POLAR GRAPH




Maximum Candela = 5612.722 Located At Horizontal Angle = 290, Vertical Angle = 71
1 - Vertical Plane Through Horizontal Angles (290 - 110) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (71) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=786.3, Medium=2964.7, High=1699.8, Very High=75.5
Back: Low=324.2, Medium=621.6, High=323.0, Very High=8.0
Uplight: Low=0.0, High=0.0

BUG Rating : B1-U0-G1