

IES ROAD REPORT

PHOTOMETRIC FILENAME : SAS-12L-U-40-T4.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST]

[TESTLAB]

[TESTDATE]

[ISSUEDATE]

[LAMPPOSITION] 0,0

[MANUFAC] Industrial Lighting Products Inc

[LUMCAT] SAS-12L-U-40-T4

[LUMINAIRE] Skyline Small, 12,000 Lumens, 4000K, Type 4 Optic

[LAMP] N/A

CHARACTERISTICS


IES Classification	Type IV
Longitudinal Classification	Short
Lumens Per Lamp	12948 (1 lamp)
Total Lamp Lumens	12948
Luminaire Lumens	12948
Downward Total Efficiency	100 %
Total Luminaire Efficiency	100 %
Luminaire Efficacy Rating (LER)	147
Total Luminaire Watts	88.2
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	8884.77
Maximum Candela Angle	50H 68V
Maximum Candela (<90 Degrees Vertical)	8884.77
Maximum Candela Angle (<90 Degrees Vertical)	50H 68V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Lamp Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	1954.74 (15.1% Lamp Lumens)
Cutoff Classification (deprecated)	Semi-Cutoff

IES ROAD REPORT
PHOTOMETRIC FILENAME : SAS-12L-U-40-T4.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	778.8	6.0	6.0
FM - Front-Medium (30-60)	4372.8	33.8	33.8
FH - Front-High (60-80)	5250.0	40.5	40.5
FVH - Front-Very High (80-90)	257.9	2.0	2.0
BL - Back-Low (0-30)	464.9	3.6	3.6
BM - Back-Medium (30-60)	1197.7	9.3	9.3
BH - Back-High (60-80)	608.5	4.7	4.7
BVH - Back-Very High (80-90)	17.1	0.1	0.1
UL - Uplight-Low (90-100)	0.0	0.0	0.0
UH - Uplight-High (100-180)	0.0	0.0	0.0
Total	12947.7	100.0	100.0
BUG Rating	B2-U0-G3		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Lamp
Downward Street Side	10659.5	82.3
Downward House Side	2288.3	17.7
Downward Total	12947.8	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	12947.8	100.0

POLAR GRAPH




Maximum Candela = 8884.77 Located At Horizontal Angle = 50, Vertical Angle = 68
1 - Vertical Plane Through Horizontal Angles (50 - 230) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (68) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=778.8, Medium=4372.8, High= 5250.0, Very High=257.9
Back: Low=464.9, Medium=1197.7, High=608.5, Very High=17.1
Uplight: Low=0.0, High=0.0

BUG Rating : B2-U0-G3