



		EVEREST 2.0 (EVT2)	ENDEAVOUR 2.0 (EDV2)	GRID FRAME HIGH BAY (GH)	PREMIUM HIGH BAY TENNIS COURT (PHB-TC)
SUITABLE APPLICATIONS	GYMNASIUM	✓	✓	✓	✓
	FITNESS CENTER	✓	✓	✓	✓
	WAREHOUSE	✓	✓	✓	✓
	DISTRIBUTION CENTER	✓	✓	✓	✓
	MANUFACTURING PLANT	✓	✓	✓	
	RACKING	✓	✓		✓
	FOOD PROCESSING		✓		
	COOLERS / FREEZER	✓			
	SAW MILL		✓		
	TENNIS COURT				✓
	RACQUETBALL COURT			✓	
	RECESSED			✓	
FEATURES & PERFORMANCE	LUMEN RANGE	12,000 - 60,000	8,000 - 100,000	12,000 - 26,000	65,000 - 91,000
	EFFICACY (lm/W) UP TO	167 LPW	164 LPW	158 LPW	137 LPW
	CRI	>80	>80	>80	>80
	CCT OPTIONS	40, 50	30, 35, 40, 50	30, 35, 40, 50	30, 35, 40, 50
	DISTRIBUTION	Wide & Narrow	Wide & Narrow	Wide	Indirect
	VOLTAGE	120-277V - Opt. 277-480V	120-277V - Opt. 347-480V	120-277V - Opt. 347-480V	120-277V - Opt. 347-480V
	SIZES	1FT, 2FT & 3FT	2FT & 4FT	2x2 & 2x4	4FT
	HOUSING	Linear	Linear	Linear	Linear
	LENSING	Frosted Acrylic, Polycarbonate, Diffuse Narrow Distribution	Frosted Acrylic & Polycarbonate	Frosted Acrylic & Clear Polycarbonate	Clear Polycarbonate
	DEDICATED UPLIGHT OPTION		✓		
	LIFE (L70)	>100K	>100K	>100K	>100K
	AMBIENT RANGE	-40°F - 122°F	-40°F - 149°F	-40°F - 125°F	-40°F - 115°F
	EMERGENCY	✓	✓	✓	
	RATINGS	Damp, IP5X	Damp, IP5X, IK10	Damp	Damp
	BAA COMPLIANT		✓	✓	✓
	BABA COMPLIANT			✓	✓
	DLC	Premium	Premium	Standard & Premium	Unlisted
BASIC CONTROLS	ON/OFF OCCUPANCY	✓	✓	✓	✓
	ON/OFF OCCUPANCY W/ PHOTOCELL	✓	✓	✓	✓
	ON/OFF OCCUPANCY W/ DAYLIGHT HARVESTING	✓	✓	✓	✓
	DAYLIGHT HARVESTING	✓	✓	✓	✓
	BI-LEVEL OCCUPANCY	✓	✓	✓	✓
	BI-LEVEL OCCUPANCY W/ PHOTOCELL	✓	✓	✓	✓
ADVANCE GROUPING CONTROLS	EASYSENSE	✓	✓	✓	✓
	ENLIGHTED		✓	✓	
	LUTRON	✓	✓	✓	