



STRIPS

COMMERCIAL

SELECTION GUIDE

COMING SOON

	DISCOVERY (DSC)	QWIKLINK LINEAR STRIP (QL)	VS STRIP (VS)	SLIM STRIP (SS)	FX LOW PROFILE STRIP (FX)	
SUITABLE APPLICATIONS	EDUCATION	✓	✓	✓	✓	
	HEALTHCARE	✓	✓	✓	✓	
	COMMERCIAL OFFICE	✓	✓	✓	✓	
	RETAIL	✓	✓	✓	✓	
	STORAGE FACILITY	✓	✓	✓	✓	
	GROCERY STORE	✓	✓	✓	✓	
	RESIDENTIAL	✓	✓	✓	✓	
	STAIRWELL	✓	✓	✓	✓	
INDUSTRIAL	✓	✓	✓	✓	✓	
FEATURES & PERFORMANCE	LUMEN RANGE	2,000 - 17,000	1,200 - 5,200 (Lumen Selectable)	2,600 - 12,000	3,300 - 12,000	1,800 - 10,000
	EFFICACY (lm/W) UP TO	169	130	133	135	149
	CRI	>80	>80	>80	>80	>80
	CCT OPTIONS	30, 35, 40, 50	30, 35, 40 (CCT Selectable)	40, 50	35, 40, 50	40, 50
	VOLTAGE	120-277V - Opt. 347-480V	120-277V	120-277V - Opt. 347-480V	120-277V - Opt. 347-480V	120-277V - Opt. 347-480V
	DIMMING RANGE	100%-10% standard (1% Dim Opt)	100%-10%	100%-10%	100%-10%	
	AMBIENT RANGE	-4°F - 120°F	-4°F - 131°F	-4°F - 122°F	-4°F - 122°F	-4°F - 118°F
	SIZES	2FT, 4FT & 8FT	2FT & 4FT	2FT, 4FT & 8FT	4FT & 8FT	4FT & 8FT
	WIDTH	4.3"	2.5"	3.36"	2.36"	2.9" & 4.3"
	LENS STYLE	Flat	Flat	Round	Round	
	UPLIGHT WITH LENS	4%	10%	12%	9%	4%
	MOUNTING	Continuous Run, Pendant, Surface, Suspended	Continuous Run, Pendant, Surface, Suspended	Continuous Run, Pendant, Surface, Suspended	Continuous Run, Pendant, Surface, Suspended	Continuous Run, Pendant, Surface, Suspended
	SENSOR MOUNTING	Integral & End	End	End	End	End
	RATINGS	Damp, ETL	Damp, ETL	Damp, ETL	Damp, ETL	Damp, ETL
	DLC	Standard & Premium	Standard & Premium	Standard	Standard	Unlisted
BAA COMPLIANT	✓				✓	
RETROFIT KIT OPTION	✓		✓		✓	
BASIC CONTROLS	ON/OFF OCCUPANCY	✓	✓	✓	✓	
	DAYLIGHT HARVESTING	✓	✓	✓	✓	
	BI-LEVEL OCCUPANCY	✓	✓	✓	✓	
	BI-LEVEL OCCUPANCY WITH PHOTOCELL	✓	✓	✓	✓	
ADVANCE GROUPING CONTROLS	EASYSENSE	✓				
	ENLIGHTED	✓				
	LUTRON	✓				

STRIPS SELECTION GUIDE