






STRIP SELECTION GUIDE

	FZ	QL	VS 	SS 	FX 	
SUITABLE APPLICATIONS	EDUCATION	✓	✓	✓	✓	
	HEALTHCARE	✓	✓	✓		
	COMMERCIAL OFFICE	✓	✓	✓	✓	
	RETAIL	✓	✓	✓	✓	
	STORAGE FACILITY	✓	✓	✓	✓	
	GROCERY STORE	✓	✓	✓	✓	
	RESIDENTIAL		✓	✓	✓	
	STAIRWELL	✓	✓			
	INDUSTRIAL	✓	✓	✓	✓	
FEATURES & PERFORMANCE	LUMEN RANGE	2,000 - 17,000	1,200 - 5,200 (Field Selectable)	2,600 - 12,000	3,300 - 12,000	1,800 - 10,000
	EFFICACY (lm/W) UP TO	169	130	133	135	149
	CRI	>80	>80	>80	>80	>80
	CCT OPTIONS	30, 35, 40, 50	30, 35, 40 (Field Selectable)	40, 50	35, 40, 50	40, 50
	VOLTAGE	120-277V - Opt. 347-480V	120-277V	120-277V - Opt. 347-480V	120-277V - Opt. 347-480V	120-277V - Opt. 347-480V
	DIMMING RANGE	100%-10% std. (1% Dim Opt)	100%-10%	100%-10%	100%-10%	N/A
	AMBIENT RANGE	-4°F - 120°F	-4°F - 131°F	-4°F - 122°F	-4°F - 122°F	-4°F - 118°F
	SIZES	2FT, 4FT & 8FT	2FT & 4FT	2FT, 4FT & 8FT	4FT & 8FT	4FT & 8FT
	WIDTH	4.3"	2.5"	3.36"	2.36"	2.9" & 4.3"
	LENS STYLE	FLAT	FLAT	ROUND	ROUND	N/A
	UPLIGHT WITH LENS	4%	10%	12%	9%	4%
	MOUNTING	CONTINUOUS RUN, PENDANT, SURFACE, SUSPENDED	CONTINUOUS RUN, PENDANT, SURFACE, SUSPENDED	CONTINUOUS RUN, PENDANT, SURFACE, SUSPENDED	CONTINUOUS RUN, PENDANT, SURFACE, SUSPENDED	CONTINUOUS RUN, PENDANT, SURFACE, SUSPENDED
	SENSOR MOUNTING	INTEGAL & END	END	END	END	END
	RATINGS	DAMP, ETL	DAMP, ETL	DAMP, ETL	DAMP, ETL	DAMP, ETL
	DLC	PREMIUM	PREMIUM	PREMIUM	PREMIUM	PREMIUM
BAA COMPLIANT	YES	NO	NO	NO	YES	
RETROFIT KIT OPTION	YES	NO	YES	NO	YES	
BASIC CONTROLS	ON/OFF OCCUPANCY	✓	✓	✓ ¹	✓ ¹	✓ ¹
	DAYLIGHT HARVESTING	✓ ¹		✓ ¹	✓ ¹	
	BI-LEVEL OCCUPANCY	✓	✓	✓ ¹	✓ ¹	✓ ¹
	BI-LEVEL OCCUPANCY WITH PHOTOCELL	✓	✓	✓ ¹	✓ ¹	
ADVANCE GROUPING CONTROLS	EASYSENSE	✓				
	ENLIGHTED	✓				
	LUTRON	✓				

¹ End fixture mounted. Cannot be utilized when fixtures are mounted in continuous runs