



VAPORTIGHT

INDUSTRIAL

SELECTION GUIDE

	AMAZON Z SERIES (WTZ)	BLIZZARD (BL)	VALUE VAPOR TIGHT (VVT)	ROUND HIGH BAY (RB4)	AMAZON X SERIES (WTX)	
SUITABLE APPLICATIONS	COOLERS & FREEZERS	✓	✓	✓	✓	
	FOOD & BEVERAGE PREPARATION	✓	✓	✓	✓	
	GREENHOUSE	✓	✓	✓	✓	
	PHARMACEUTICAL	✓	✓	✓	✓	
	HEALTHCARE	✓	✓	✓	✓	
	EDUCATION	✓	✓	✓	✓	
	INDUSTRIAL	✓	✓	✓	✓	
	PARKING GARAGE	✓		✓	✓	
	HOCKEY RINKS		✓			
	SAW MILLS	✓	✓	✓	✓	
FEATURES & PERFORMANCE	LUMEN RANGE	2,000 - 24,000	12,000 - 42,000	3,000 - 6,000	14,000 - 34,000	1,600 - 9,600
	EFFICACY (lm/W) UP TO	156	168	145	165	138
	CRI	>80	>80	80	>80	>80
	CCT OPTIONS	30, 35, 40, 50	30, 35, 40, 50	40, 50	35, 40, 50 CCT SELECTABLE	50
	DISTRIBUTION	Wide	Wide & Narrow	Wide	Wide	Wide
	VOLTAGE	120-277V - Opt. 347V, 480V	120-277V - Opt. 347V, 480V	120-277V - Opt. 347V, 480V	120-277V - Opt. 347-480V	120-277V - Opt. 347V, 480V
	SIZES	2FT, 4FT & 8FT	2FT & 4FT	2FT & 4FT	10" - 13"	4FT & 8FT
	HOUSING	Linear	Linear	Linear	Round	Linear
	LENSING	Clear & Frosted Acrylic, Clear & Frosted Polycarbonate	Clear & Frosted Acrylic, Clear & Frosted Polycarbonate	Frosted Acrylic	Frosted & Clear Polycarbonate	Clear & Frosted Acrylic, Clear & Frosted Polycarbonate
	LIFE	>100K	>100K	>100K	>100K	>100K
	AMBIENT RANGE	-40°F - 131°F	-40°F - 140°F	-4°F - 104°F	-40°F - 122°F	-4°F - 104°F
	EMERGENCY	✓	✓		✓	✓
	RATINGS	WET, IP65, IP66, IP67, NSF	WET, IP65, IP66, IP67, IP69, IK10, NSF	WET, IP65, NSF	WET, IP65, NSF, IK10	WET, IP65, IP66, IP67, NSF
	BAA COMPLIANT	✓	✓			✓
DLC	Standard & Premium	Standard & Premium	Standard	Standard & Premium	Unlisted	
BASIC CONTROLS	ON/OFF OCCUPANCY	✓	✓	✓	✓	
	ON/OFF OCCUPANCY W/ PHOTOCELL	✓	✓		✓	
	BI-LEVEL OCCUPANCY	✓	✓	✓	✓	
	BI-LEVEL OCCUPANCY W/ PHOTOCELL	✓	✓		✓	
ADVANCE GROUPING CONTROLS	EASYSENSE	✓	✓			
	ENLIGHTED	✓	✓			

VAPOR TIGHT SELECTION GUIDE