

WALL PACKS



OUTDOOR

SELECTION GUIDE



WALL PACKS SELECTION GUIDE

	VIEWPOINT WALL PACK (VWM)	SKYLINE WALL MOUNT (SAS/SAM)	FULL CUTOFF WALL PACK (WPCS/WPCM)	SLIM WALL PACK (SWP)	OW SERIES WALL PACK (OWS, OWM, OWL)
SUITABLE APPLICATIONS	PEDESTRIAN WALKWAYS	✓		✓	✓
	BUILDING ENTRANCES	✓		✓	✓
	MULTI-USE FACILITIES	✓	✓	✓	✓
	PARKING LOTS	✓	✓	✓	
	STORAGE FACILITIES	✓	✓	✓	✓
	INSTITUTIONS	✓	✓	✓	
	SCHOOLS	✓	✓	✓	✓
	LOADING DOCKS	✓		✓	✓
	WAREHOUSES	✓	✓	✓	✓
SHOPPING CENTERS	✓	✓	✓	✓	
HOUSING SIZES	1	2	2	2	3
LUMEN PACKAGES	Medium: 3L-14L	Small: 6L-18L Medium: 24L-50L	Small: 3L-5L Medium: 3L-11L	Small: 2L-3L Medium: 5L-10L	Small: 1L-4L Medium: 3L-5L, Large: 5L-16L
LPW (UP TO)	147 LPW	165 LPW	159 LPW	150 LPW	147 LPW
LUMEN SELECTABLE	✓	Optional with FAO	No	Optional with FAO	✓
CRI	>70	>70	>70	>70	>70
CCT OPTIONS	3K, 4K, 5K CCT Selectable	3K, 4K, 5K	3K, 4K, 5K	3K, 4K, 5K CCT Selectable	3K, 4K, 5K CCT Selectable
DISTRIBUTIONS	T3, T4	T2, T3, T4, FTA	T2, T3, T4	T4	T4
DISTRIBUTION PERFORMANCE	Moderate Uniformity and Targeted Performance	Excellent Uniformity and Targeted Performance	Moderate Uniformity and Targeted Performance	Low Uniformity and Targeted Performance	Low Uniformity and Targeted Performance
IDA	✓	✓	✓	Optional with Hood	Optional
VOLTAGES	120-277V or 277-480V	120-277V or 347-480V	120-277V or 347-480V; Dual Driver	120-277V or 277-480V	120-277V or 277-480V
MOUNTING	Drill Through Back Casting	Bracket with No Through Drilling	Drill Through Back Casting	Bracket with No Through Drilling	Drill Through Back Casting
BATTERY BACKUP	14W; 14W Cold Temp -20°F		Small: 5W, Medium: 5W-12W; 14W Cold Temp -20°F	Small: None Medium: 10W; 10W Cold Temp -20°F	Small: None, Medium: 5W-10W; 10W Cold Temp -20°F, Large: 5W-10W; 10W Cold Temp -20°F
SURGE PROTECTION	6kV	6kV	4kV	2.5kV	6kV (2.5kV OWS)
LED LIFETIME	L70 > 100K	L82 > 100K	L70 > 100K	L70 > 100K	L70 > 100K
AMBIENT RANGE	-40 to +40°C	-40 to +50°C	-40 to +50°C	-40 to +40°C	-40 to +45°C
RATINGS	IP65	IP66	Wet Location	IP65	IP65
BAA COMPLIANT		✓	✓		
FINISHES	Bronze Standard, Upcharge for Black, White & Silver	Bronze, Black, White, Silver & Custom Color	Bronze, Black, White, Silver & Custom Color	Bronze Standard; Upcharge for Black, White, Silver & Custom Color	Bronze Standard; Upcharge for Black, White, Silver & Custom Color (OWM/OWL)
DLC		Premium	Premium	Premium	Premium
PHOTOCELL	Electronic Pencil Photocell	3/7-Pin Control Receptacle	Electronic Pencil Photocell	Electronic Pencil Photocell	Electronic Pencil Photocell
FAO (FIELD ADJUSTABLE OUTPUT)		7 Levels		7 Levels	
OCCUPANCY SENSOR	Field Adjustable Bluetooth Programmable Sensor	Field Adjustable Bluetooth Programmable Sensor	Field Adjustable Bluetooth Programmable Sensor	Field Adjustable Bluetooth Programmable Sensor	External Field Adjustable Bluetooth Programmable Sensor
ADVANCE GROUPING CONTROLS	ENLIGHTED		Integrated or via control receptacle		
	SYNAPSE		Integrated or via control receptacle	Integrated	